

EZ OFF Pole Guard for 3" Poles

Thank you for purchasing the EZ OFF Predator Guard. Pole Guards are most effective when placed as high up as possible on the pole. The tube of the EZ Off is made from aluminum, please use your favorite car wax on the tube to keep it free from weatherization.

Step 1) Using a tape measure, measure your pole and mark with a pencil at 57" from the ground up.



Step 2) Using a square mark all 4 sides of your pole at your 57" mark.



Step 3) Remove the clamp assembly from the hardware bag, and undo the wing nut and remove the bolt. Slide the clamp around the pole, where the pencil mark is, re-insert the bolt and thread the wing nut back on. Notice that the bolt with the wing nut is placed on the same side that your cable comes down the pole. Tighten the insert lock nut using a 7/16 wrench and finger tighten the wing nut.



Step 4) Using your pencil mark, make sure your brackets are level. Open your tube, first open the adjustable latch, then slide the bolt down and out

of the hidden keyhole at the bottom of the pole guard. Slip the guard around the pole and let the top plates rest on the clamps

Step 5) Align the notch in the top plate so that it is on the same side as the cable.



Step 6) Bring the 2 halves together. The notch should be to the front of the cable. Attach the latch but do not close it



Step 7) As the latch holds the upper section of the pole guard in place you need to insert the pin into the hidden keyhole. Place the rounded end of the pin into the larger part of the keyhole, and slide the pin upward which locks the pin into place.



Step 8) Snap the lock shut. Your EZ OFF pole guard is all set up. When you monitor your housing, remove the EZ OFF before lowering.

EZ OFF Pole Guard for 3" Poles



To do nest checks, remove the tube. Loosen the wing nut and let your bracket slide down the pole and rest on the cable guide. When done with nest check, raise up your housing, slip the bracket into place using your pencil mark on the pole, and tighten the wing nut.

